

## UF-B 2 Conductor w/Ground

Regency's Type UF cables are intended for use in accordance with Article 339 and other applicable parts of the National Electrical Code in wiring systems operating at a potential of 600 V or less.

**Conductor construction** is soft drawn bare copper meeting the requirements of ASTM Specifications B-3 and B-787. Gauge sizes 14 and 10 are solid copper conductors. Sizes 8 thru 6 are stranded conductors. All ground wires are solid.

The insulation is a color coded THHN / THWN type for wet, dry or corrosive applications of up to 600 volts and conductor temperatures up to 75° C. The outer jacket is a sunlight resistant, high quality polyvinylchloride (PVC).

**Application:** Suitable for use as direct burial or indoor branch circuit wiring.

**Conductor:** Soft drawn bare copper (ASTM Spec. B-3)  
Solid (14 awg thru 10 awg), Stranded (8 awg and 6 awg), Solid ground

**Insulation:** Polyvinylchloride (PVC) with a nylon sheath

**Outer Jacket:** Polyvinylchloride (PVC)

**Temperature:** 75° C

**Voltage:** 600 volts

Gauge Size	Conductor Stranding	Ground Size
14	Solid	14
12	Solid	12
10	Solid	10
8	Stranded	10
6	Stranded	10

