

Regency Wire & Cable

830 South West Street, Sikeston MO 63801

800-876-3020 / 573-472-2990 / FAX 573-471-3134



Toro™ GDC Decoder Cable

Description:

Regency's Toro™ GDC Cable is manufactured for the control of Toro's™ decoder systems. It is direct burial rated.

Conductor construction is soft drawn bare copper meeting the requirements of ASTM Specification B-3. Toro™ GDC Decoder Cable features solid copper conductors.

The two conductors shall be insulated with a low density, high molecular weight polyethylene (PE). One conductor will be insulated black and the other conductor insulated white. The two conductors are twisted with a 4" lay and rated for systems applications up to 600 volts.

The two twisted conductors shall be extruded with a high density, sunlight resistant polyethylene (HDPE) jacket. The jacket comes in a variety of colors to accommodate easy identification. Comes with pull cord for easy stripping.

Toro™ GDC Decoder Cable is constructed in accordance with Underwriters Laboratories, Inc.

Application:

Suitable for use as Toro's™ communication wire for control of Toro decoder systems.

Construction:

Conductor: Soft drawn bare copper (ASTM Spec. B-3).
Two (2) conductors
Solid (14 awg)

Insulation: Polyethylene (PE)

Outer Jacket: High Density Polyethylene (HDPE)

Temperature: 75 C

Voltage: 600 volts

Jacket Colors: Red, blue, green, and yellow.

Gauge Size	Conductor Insulation	Outer Jacket
14	.045	.035